

- WASSERTECHNIK-





CREATED FOR THE MOST DEMANDING CUSTOMERS WHO WANT TO GET THE BEST COFFEE BREW, AND AT THE SAME TIME PERFECTLY PROTECT THE MACHINE AGAINST ALL DEPOSITS AND CORROSION

DUE TO THE VERY LOW OPERATING COSTS, IT IS RECOMMENDED WHEREVER THERE IS A HIGH DEMAND FOR TREATED WATER.

THE COFFEE GENIUS BASED ON NANO-MOLECULAR TECHNOLOGY. IT LEAVES FAR-REACHING, WIDELY USED SOLUTIONS CONSISTING OF CARTRIDGES REPLACEMENT.

# CREATE FOR DEMANDING CUSTOMERS!

PROFESSIONAL BARISTAS KNOW WELL THAT IN ORDER TO GET THE PERFECT BREW, YOU NEED TO PREPARE / TREAT WATER VERY PRECISELY.

IT IS THE ONLY SYSTEM ON THE MARKET THAT PROVIDES OPTIMAL WATER PARAMETERS ACCORDING TO THE MOST DEMANDING STANDARDS.

## **COFFEE GENIUS:**

- **♦** NEUTRAL PH
- ▲ REDUCED OF CARBONATE HARDNESS
- ♦ OPTIMAL AMOUT OF MINERALS. TOO MUCH MINERAL WILL PROVIDE THICKER COFFEE WITH STRONG CREMA, BUT THE BREW WILL BE DEPRIVED OF THE BEST FLAVORS AND AROMAS. WITH A SMALL AMOUNT OF MINERALS, YOU CAN GET COFFEE WITH INTENSE FLAVORS AND AROMAS, BUT LESS INTENSE COLOUR AND WITH LITTLE CREMA. OBTAINING THE OPTIMAL BREW QUALITY IS VERY DIFFICULT.
- ♦ REMOVING ALL CHEMICAL AND ORGANIC IMPURITIES AFFECTING THE TASTE AND SMELL OF WATER (COFFEE)
- **♦ VERY LOW OPERATING COSTS**



### **PRE - FILTRATION**

PREFILTER AF - C2 FOR CFG 120 / 90 / 60



A SET OF 3 FILTERS FOR CFG 24



# PRESSURE STORAGE TANKS

#### **TECHNICAL PARAMETERS:**

| MODEL | GROSS CAPACITY | NET CAPACITY [L] | DIMENTIONS / DIAMETER / HIGH / [mm] | CONNECTIONS<br>[INCH] |
|-------|----------------|------------------|-------------------------------------|-----------------------|
| RO 12 | 15             | 12               | 250 / 400                           | 1 / 4"                |
| RO 30 | 38             | 30               | 400 / 600                           | 3 / 4"                |





**RO 12** 

**RO 30** 

# **NANO - MOLECULAR FILTRATION - CFG SERIES**

#### TECHNICAL PARAMETERS:

| MODEL   | EFFICIENCY* [L/h]<br>FOR WATER TEMP. OF 15° | MAX INLET WATER TEMPERATURE [C°] | DIAMETER<br>CONNECTIONS [INCH] | DIMENTIONS / D / W / H / [mm] |
|---------|---|----------------------------------|--------------------------------|-------------------------------|
| CFG 120 | 120   | < 30                             | 1/2;3/8                        | 510 / 140 / 500               |
| CFG 90  | 90  | < 30                             | 1/2;3/8                        | 510 / 140 / 500               |
| CFG 60  | 60  | < 30                             | 1/2;3/8                        | 510 / 280 / 500               |
| CFG 24  | 24  | < 30                             | 1/4 lor 3/8                    | 150 / 425 / 460               |









CFG 120 CFG 90 CFG 60



WASSERPURE EUROPE SP. Z O. O.

UL. SIENKIEWICZ 49 | 42-600 GÓRY TARNOWSKIE
TEL. 0048 575 500 676 | EUROPE@WASSERPURE.COM

WASSERPURE.COM